
# Air Conditioners BKC Series Explosion-proof Window Air Conditioners



- Explosion protection to
  - -CENELEC
  - -IEC
- Can be used in
  - Zone 2
- For explosion-proof window air conditioner, the corresponding product is the cooling-only air conditioner in T1 and T3 group. It is mainly used in high temperature areas, such as Middle East, Middle Africa, Southeast Asia and tropical zone nearby the equator.
- Explosion-proof window air conditioner is based on renowned brand, by conducting explosion-proof treatment to internal control units compressor, indoor and outdoor fan motors, temperature sensor system, protective system, heat-removal system, cooling system, etc., after which the outline dimensions and installation are the same as the prototype.

## Catalogue number logic





# Dimension drawings (all dimensions in mm) - subject to alteration

# Zone 2

# Air Conditioners BKC Series Explosion-proof Window Air Conditioners

### Technical data

Explosion-proof window air conditioners BKC-□/□

**Explosion protection** 

(Ex) II 3 G Ex d nC IIB T4 Gc

Certificates

LCIE 11 ATEX 1002X; IECEX CQM 11.0021X; RU C-CN.ГБ08.В.01105 (CU-TR)

KZ.7500525.22.01.00377 (CU-TR)

Conformity to standards

EN 60079-0, EN 60079-1, EN 60079-15 IEC 60079-0, IEC 60079-1, IEC 60079-15

Technical data			
Туре		BKC-50/220	BKC-70/220
Cooling capacity	W	5400	7000
	вти	18000	24000
Rated voltage/Frequency (V/Hz)		220~240/50	220~240/50
Input power (P)		2P	3P
Cooling input power (W)		2750	3770
Rated current (A)		12.8	17.4
Application areas (m²)		22~32	30~40
Sound level (dB)	Indoor unit	≤53	≤57
	Outdoor unit	≪60	≪63
Outline dimensions (L x W x H) (mm)		730×680× 450	730×680×450
Weight (kg)		50.00	55.00

**Note**: The above technical data is for normally supplied products of T3 ( $-7^{\circ}$ C $\sim$ +55 $^{\circ}$ C) temperature class, voltage is 220 $\sim$ 240V AC/50Hz, other voltages are available, such as 220 $\sim$ 240V AC/60Hz, please specify when ordering. The above data is only for reference, the actual product shall prevail.



General Catalogue 01.01.2016 http://www.waromgroup.com 8/5